

## **DLi 5-25**

The DLi 5-25 is a high-quality desktop power supply that is compatible with the DLP®Discovery™ 3000 and 4000 products, when combined with the included 8 pin molex adapter extension. Supported input voltage lies between 100-240 VAC with an internal primary current fuse.

The power supply is configured to provide the ideal output power for the DLP®Discovery™ 3000 and 4000 products. The DLi 5-25 is capable of generating an output voltage of 5 volts, 5 amps, and a maximum power of 25 watts. This output is regulated with low ripple at 1% Vp-p max for output current greater than 0.175A. For safety, the output power is protected by both over-current protection as well as short circuit protection.

The DLi 5-25 is built to satisfy the unique demands of many users. The system is encased in an impact resistant polycarbonate enclosure and contains superior quality medical grade components in order to meet the high standards established by DLi. As such, the system meets Medical Safety Agency requirements, complies with all EMI/RFI regulations, and is CE compliant. Overall safety is approved under TUV EN60601-1 and cURus 2601.

**The power supply is covered by a three-year warranty.**

### **Environmental:**

Operating Temperature	0° to 40° C with no derating
Storage Temperature	-30° to +85°
Relative Humidity	5% to 95% non-condensing
Altitude	0-10,000 feet
Cooling	Conventional

### **Dimensions (excluding cord):**

4.20L x 2.60W x 1.46H (in)  
107L x 66W x 37H (mm)

Cord Length 3.2ft / 1m

### **Weight (excluding cord):**

Max. 10 ounces, 285 grams

